

ONC Standard Convector



Features

Color

- Standard: white.
- Optional (upcharge applicable): almond, metallic silver, bronze, aluminum, semi-gloss black, metallic charcoal, sand.
- Custom colors available upon request.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 120V, 208V, 240/208V, 277V, 347V, 480V, 600V, 60 Hz, 1-phase.

Construction

- 20-gauge steel.
- Warm air outlet that directs the air to the center of the room.
- Bar grilles prevent insertion of foreign objects.
- High-limit temperature control with automatic reset.

Heating element

- 2 stainless steel tubular heating elements with aluminum fins.
- Floating heating element on high-temperature nylon bushings reducing expansion noises.

Watt density

- 700W/ft. (2320W/m).

Control

- Built-in non programmable electronic thermostat for the 120V to 240V models (-TH models).
- Wall thermostat (not included).

Installation

- 4 in. (102 mm) minimum clearance to floor and from an adjacent wall
- Quick surface-mounted installation, with the included wall mounting bracket.

Warranty

- 5-year warranty against defects.

Ouellet highly recommends the use of an electronic wall thermostat for greater comfort.

Application

- Kitchen, living room, family room, bedroom, basement.

Models

Volts	Watts	Product #		Price		Length		Weight	
		Without thermostat	Price	Built-in thermostat	Price	in.	mm	lb	kg
120	500	ONC0502BL	168.00	ONC0502BL-TH	231.00	18	457	13	6
120	1000	ONC1002BL	216.00	ONC1002BL-TH	279.00	23 9/16	598	16.7	7.6
120	1500	ONC1502BL	243.00	ONC1502BL-TH	306.00	29 1/16	739	20	9.12
208	500	ONC0508BL	168.00	ONC0508BL-TH	231.00	18	457	13	6
208	1000	ONC1008BL	216.00	ONC1008BL-TH	279.00	23 9/16	598	16.7	7.6
208	1500	ONC1508BL	243.00	ONC1508BL-TH	306.00	29 1/16	739	20	9.12
208	2000	ONC2008BL	280.00	ONC2008BL-TH	343.00	34 5/8	880	24	10.9
240/208	500/375	ONC0500BL	183.00	ONC0500BL-TH	246.00	18	457	13	6
240/208	1000/750	ONC1000BL	202.00	ONC1000BL-TH	265.00	23 9/16	598	16.7	7.6
240/208	1500/1125	ONC1500BL	231.00	ONC1500BL-TH	294.00	29 1/16	739	20	9.12
240/208	2000/1875	ONC2000BL	265.00	ONC2000BL-TH	328.00	34 5/8	880	24	10.9
347	500	ONC0507BL	215.00	-	-	18	457	13	6
347	1000	ONC1007BL	263.00	-	-	23 9/16	598	16.7	7.6
347	1500	ONC1507BL	290.00	-	-	29 1/16	739	20	9.12
347	2000	ONC2007BL	327.00	-	-	34 5/8	880	24	10.9
600	1000	ONC1006BL	263.00	-	-	23 9/16	598	16.7	7.6
600	1500	ONC1506BL	290.00	-	-	29 1/16	739	20	9.12
600	2000	ONC2006BL	327.00	-	-	34 5/8	880	24	10.9

Options

Product # Kit	Product # Factory installed*	Price	Description
KIT-ONC-TRIAC-347	TRIAC	75.00	Single-pole electronic relay, coil 24V, without transformer, 15A at 347V max.
KIT-ONC-TRIAC-347T	TRIACT	100.00	Single-pole electronic relay, coil 24V, with transformer, 15A at 208V, 240V, 277V, 347V
KIT-ONC-TRIAC-600	TRIAC	135.00	Single-pole electronic relay, coil 24V, without transformer, 6A at 600V max.

* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.

Standard color is white.

Upcharge applicable for optional colors shown in the color chart section.

Other voltages available upon request.

